



Central County Transportation Authority
Purchasing Division
241 W. South Street
Kalamazoo, MI 49007
Phone: 269.337.8020
www.kmetro.com

ADDENDUM #1
January 22, 2026

TO: ALL Prospective Bidders
PROJECT: Propane Powered Forklift
BID REFERENCE #: 56083-001.0
BID OPENING DATE/TIME: February 12, 2026 @ 3:30 p.m. Local Time.

The purpose of this addendum is to clarify and/or modify the Drawings and/or Specifications for this project. All work affected is subject to all applicable terms and conditions of the Bidding and Contract Documents.

1. REVISED: Section III – SPECIFICATIONS & REQUIREMENTS – 1. SPECIFICATIONS – Changes in RED – Added – Lifting Capacity – Minimum of 10,000 lbs. – See Attachment A

Questions related to this addendum may be addressed to Rob Branch, Deputy Director of Fleet and Facilities at (269) 337-8235, or branchr@kmetro.com or Kyle Dunn, Buyer, at (269) 337-8720, or dunnk@kalamazoocity.org.

The Addendum can be viewed and downloaded from the City’s website at <https://www.kalamazoocity.org/bidopportunities>.

In order for a bid to be responsive, this signed and dated addendum must be returned with your bid. If you have already submitted your bid, acknowledge receipt and acceptance of this addendum by signing in the place provided and returning it to the undersigned and it shall be incorporated in your bid. Please identify your return envelope with the bid reference number and project description.

Sincerely,

Greg Vliestra
Director of Support Services
c: Rob Branch, CCTA

FIRM: _____

SIGNED: _____

NAME: _____

DATE: _____

(Type or Print)



ADDENDUM #1

Attachment A

Revised Specifications & Requirements

Bid Ref#56083-001.0

Propane Powered Forklift

REVISED
SECTION III
SPECIFICATIONS AND REQUIREMENTS

1. SPECIFICATIONS

- Brakes – Oil-Cooled Disc Brakes
- Tires – Treaded/ lugged solid tires both front and rear
- Mast – 3-Stage Wide View Full Free Triple MFH 256" OAL 114" FFH 82"
- Tilt Cylinders – 5° Forward / 6° Back
- Side shifter – Integral Side shifting Fork Positioner 51" Wide - Class III
- Carriage – Included with Integral Attachment
- Forks – Hook Type - Pallet - 2.0" x 6" x 47"
- Load Backrest – Included with Fork Positioner
- Overhead Guard – Standard Height - 85"
- Hydraulic Lines – 4-Way For Side shifting Fork Positioner
- Hydraulic Control Valve – 4 Section with 4 Levers
- Mirrors – Large Side Mirrors
- Seat – Vinyl Suspension Seat with Hip Restraint
- Direction Control – Standard - Lever Direction Control
- Grab Bar – Rear Grab Bar with Horn Button
- LP Tank Cradle – Standard Mounting
- Warning Lights – Amber Strobe - Mounted Below OHG
- Warning Device – Back-Up Alarm (Outside Mount)
- Front Work Lights – (2) Front Flood Lights - LED
- Rear Work Lights – (1) Rear Flood Light – LED
- Radiator – Heavy Duty Cooling
- Transmission safety device – Speed Control with Anti-Directional Change Controller
- **Lifting Capacity – Minimum of 10,000 lbs.**

Warranty Requirements:

Standard 2 Year / 3,000 Hour, Powertrain 3 Year / 6,000 Hour, Oil Cooled Disc Brakes 5 Year / 10,000 Hour